

# KOHLER® COMMAND PRO®

## Vertical Single Cylinder Specification 13, 15 HP

MODEL	CV13	CV15
MAX. POWER @ 3600 RPM hp (kW)	13.00 (9.75)	15.00 (11.20)
DISPLACEMENT cu. in. (cc)	24.30 (398.00)	26.00 (426.00)
BORE in. (mm)	3.43 (87.00)	3.55 (90.00)
STROKE in. (mm)	2.64 (67.00)	2.64 (67.00)
MAX TORQUE lbs. ft. (Nm)	20.80 (28.20) @ 2600 RPM	23.80 (32.27) @2400 RPM
COMPRESSION RATIO	8.5:1	8.5:1
DRY WEIGHT lbs. (kg)	87.00 (39.50)	87.00 (39.50)
OIL CAPACITY U.S. quarts (liters)	4.00 (1.90)	4.00 (1.90)
LUBRICATION	Full pressure w/full-flow filter	Full pressure w/full-flow filter
*DIMENSIONS L x W x H	17.69" x 17.60" x 13.66"	17.69" x 17.60" x 13.66"

\*Height includes recoil starter to PTO mounting face (Subtract 1.36" for no recoil). Length measures valve cover to base of blower housing. Width includes muffler. (Subtract 2.69" if no muffler).

## Vertical Twin Cylinder Specifications 17, 18, 20, 22, 25, 26 HP

MODEL	CV17	CV18	CV20	CV22	CV25	**CV26
MAX. POWER @ 3600 RPM hp (kW)	17.00 (12.70)	18.00 (13.40)	20.00 (14.90)	22.00 (16.40)	25.00 (18.40)	26.00 (19.40)
DISPLACEMENT cu. in. (cc)	34.20 (561.00)	38.00 (624.00)	38.00 (624.00)	41.10 (674.00)	44.00 (725.00)	44.00 (725.00)
BORE in. (mm)	2.87 (73.00)	3.03 (77.00)	3.03 (77.00)	3.15 (80.00)	3.27 (83.00)	3.27 (83.00)
STROKE in. (mm)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)
MAX TORQUE lbs. ft. (Nm)	27.50 (37.28) @ 2200 RPM	30.50 (41.35) @ 2600 RPM	32.50 (44.06) @ 2600 RPM	33.00 (44.74) @ 2600 RPM	40.00 (54.23) @ 2200 RPM	41.60 (56.40) @ 2200 RPM
COMPRESSION RATIO	8.5:1	8.5:1	8.5:1	8.5:1	9:1	9:1
DRY WEIGHT lbs. (kg)	90.00 (41.00)	90.00 (41.00)	90.00 (41.00)	90.00 (41.00)	94.00 (43.00)	94.00 (43.00)
OIL CAPACITY U.S. quarts (liters)	2.00 (1.90)	2.00 (1.90)	2.00 (1.90)	2.00 (1.90)	2.10 (2.00)	2.10 (2.00)
LUBRICATION	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter
*DIMENSIONS L x W x H	21.20" x 17.70" x 14.30"	21.20" x 17.70" x 14.30"	21.20" x 17.70" x 14.30"	21.20" x 17.70" x 14.30"	21.20" x 17.70" x 14.30"	21.20" x 17.70" x 14.30"

\*Height is to PTO mounting face. Length is air cleaner cover to base of blower housing.

### Horizontal Single Cylinder Specifications 6 HP

MODEL	CH6
MAX. POWER @ 3600 RPM hp (kW)	6.00 (44.70)
DISPLACEMENT cu. in. (cc)	10.98 (180.00)
BORE in. (mm)	2.64 (67.00)
STROKE in. (mm)	2.01 (51.00)
MAX TORQUE lbs. ft. (Nm)	8.59 (11.65)
COMPRESSION RATIO	8.5:1
DRY WEIGHT lbs. (kg)	45.00 (20.40)
OIL CAPACITY U.S. quarts (liters)	1.30 (0.60)
FUEL CAPACITY U.S. quarts (liters)	3.00 (2.80)
LUBRICATION	Splash
*DIMENSIONS L x W x H	11.49" x 14.90" x 13.60"

\*Lengths includes recoil starter to PTO face.

### Horizontal Single Cylinder Specifications 11, 13, 15 HP

MODEL	CH11	CH13	CH15
MAX. POWER @ 3600 RPM hp (kW)	11.00 (8.20)	13.00 (9.75)	15.00 (11.20)
DISPLACEMENT cu. in. (cc)	24.30 (398.00)	24.30 (398.00)	26.00 (426.00)
BORE in. (mm)	3.43 (87.00)	3.43 (87.00)	3.55 (90.00)
STROKE in. (mm)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)
MAX TORQUE lbs. ft. (Nm)	20.10 (27.25) @ 2200 RPM	20.80 (28.20) @ 2600 RPM	23.80 (32.27) @ 2400 RPM
COMPRESSION RATIO	8.5:1	8.5:1	8.5:1
DRY WEIGHT lbs. (kg)	88.30 (40.00)	88.30 (40.00)	88.30 (40.00)
OIL CAPACITY U.S. quarts (liters)	4.00 (1.90)	4.00 (1.90)	4.00 (1.90)
FUEL CAPACITY U.S. quarts (liters)	5.00 (4.70)	5.00 (4.70)	5.00 (4.70)
LUBRICATION	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter
DIMENSIONS L x W x H	13.74" x- 19.78" x 17.68"	13.74" x- 19.78" x 17.68"	13.74" x- 19.78" x 17.68"

\*Length includes recoil stater to PTO mounting face. (Subtract 2.35" for no recoil). Height measures valve cover to base of blower housing.

### Horizontal Twin Cylinder Specifications 18, 20, 22, 25, 26 HP

MODEL	CH18	CH20	CH22	CH25	**CH26
MAX. POWER @ 3600 RPM hp (kW)	18.00 (13.40)	20.00 (14.90)	22.00 (16.40)	25.00 (18.40)	26.00 (19.40)
DISPLACEMENT cu. in. (cc)	38.00 (624.00)	38.00 (624.00)	41.10 (674.00)	44.00 (725.00)	44.00 (725.00)
BORE in. (mm)	3.03 (77.00)	3.03 (77.00)	3.15 (80.00)	3.27 (83.00)	3.27 (83.00)
STROKE in. (mm)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)	2.64 (67.00)
MAX TORQUE lbs. ft. (Nm)	30.50 (41.35) @ 2600 RPM	32.50 (44.06) @ 2600 RPM	33.00 (44.74) @ 2600 RPM	40.00 (54.23) @ 2200 RPM	41.60 (56.40) @ 2200 RPM
COMPRESSION RATIO	8.5:1	8.5:1	8.5:1	9:1	9:1
DRY WEIGHT lbs. (kg)	90.00 (41.00)	90.00 (41.00)	90.00 (41.00)	94.00 (43.00)	94.00 (43.00)
OIL CAPACITY U.S. quarts (liters)	2.00 (1.90)	2.00 (1.90)	2.00 (1.90)	2.10 (2.00)	2.10 (2.00)
LUBRICATION	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter	Full pressure w/full-flow filter
*DIMENSIONS L x W x Height	13.00" x 17.70" x 18.96"	13.00" x 17.70" x 18.96"	13.00" x 17.70" x 18.96"	13.98" x 17.70" x 18.96"	13.98" x 17.70" x 18.96"

\*Length is to PTO mounting face.

\*\*Electronic fuel injection