

KOHLER® COMMAND PRO® CS

Horizontal Specifications 4, 6, 8.5, 10, 12 HP

MODEL	CS4	CS6	CS8.5	CS10	CS12
MAX. POWER @ 3600 RPM hp (kW)	4.00 (2.98)	6.00 (4.47)	8.50 (6.34)	10.00 (7.46)	12.00 (8.95)
DISPLACEMENT cu. in. (cc)	7.63 (125.00)	10.68 (175.00)	15.25 (250.00)	18.30 (300.00)	21.96 (360.00)
BORE in. (mm)	2.20 (56.00)	2.59 (66.00)	2.95 (75.00)	3.07 (78.00)	3.35 (85.00)
STROKE in. (mm)	1.97 (50.00)	1.97 (50.00)	2.24 (57.00)	2.48 (63.00)	2.48 (63.00)
MAX. TORQUE lbs. ft. (Nm)	5.50 (7.46) @ 2600 RPM	8.10 (10.98) @ 2400 RPM	12.20 (16.54) @2400 RPM	14.70 (19.93) @2400 RPM	18.40 (24.95) @2400 RPM
COMPRESSION RATIO	8.3:1	8.5:1	8.3:1	8.1:1	8.1:1
DRY WEIGHT lbs. (kg)	35.20 (15.97)	35.20 (15.97)	58.00 (26.31)	70.50 (31.98)	70.50 (31.98)
OIL CAPACITY U.S. pints (liters)	1.27 (0.60)	1.27 (0.60)	2.10 (1.00)	2.10 (1.00)	2.10 (1.00)
FUEL CAPACITY U.S. quarts (liters)	4.10 (3.90)	4.10 (3.90)	6.30 (6.00)	7.30 (6.90)	7.30 (6.90)
LUBRICATION	Splash	Splash	Splash	Splash	Splash
*DIMENSIONS L x W x H	10.24" x 15.12" x 14.69"	10.24" x 15.12" x 14.69"	11.48" x 16.97" x 16.85"	12.95" x 17.72" x 17.83"	12.95" x 17.72" x 17.83"

*Length is to PTO mounting face, including recoil starter.

Horsepower ratings (shown as gross) are in accordance with Society of Automotive Engineers Small Engine Test Code J1995. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed and ambient operating conditions (temperature, humidity and altitude). For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.