



# KOHLER COMMAND 6 HP XKE



**Cooling:** Air  
**Cylinders:** Single  
**Shaft:** Horizontal  
**Engine Type:** 4-cycle, Gasoline, OHV, Cast Iron Cylinder Liner, Aluminum Block

## Easy, Dependable Starts

- Fixed-jet, choke-equipped carburetor
- Standard fuel pump with filter and engine-mounted recoil starter

## Reliability & Long-life Design

- Stainless steel exhaust valve
- Induction-hardened crankshaft and camshaft
- Dual ball bearing crankshaft

## Peak Power Performance

- Overhead valve design
- Mahle piston
- Gasoline-powered

## User-friendly Maintenance

- Standard advanced ignition timing
- Closed crankcase breather
- 3/4" power take-off (PTO)

MODEL	XKE
MAXIMUM CORRECTED BRAKE HORSEPOWER	5.95 cbhp @4800 rpm
MAXIMUM CORRECTED TORQUE	8.02 ft-lbx @3000 rpm
MAXIMUM OPERATING SPEED	6800 rpm
OIL CAPACITY	22 to 24 ounces
BORE	2.64 in.
STROKE	2.01 in.
DISPLACEMENT	10.98 cu. in.
COMPRESSION RATIO	8.5 : 1
WEIGHT (APPROX.)	36 .bs.

Torque and horsepower obtained with exhaust system and air cleaner in place.

Horsepower ratings (shown as gross) are in accordance with Society of Automotive Engineers Small Engine Test Code J1995. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed and ambient operating conditions (temperature, humidity and altitude). For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.