

# KOHLER<sup>®</sup> MAGNUM

## Horizontal Specifications 8, 12, 16 HP

MODEL	M8	M12	M16
MAX. POWER @ 3600 RPM HP	8.00 (6)	12.00 (9)	16 (11.9)
DISPLACEMENT cu. in.	18.64 (305.4)	29.07 (476.5)	35.9 (588.2)
BORE in.	2.94 (74.61)	3.38 (85.73)	3.75 (95.25)
STROKE in.	2.75 (69.85)	3.25 (82.55)	3.25 (82.55)
MAX. TORQUE lbs. ft.	13.60 (18.44) @ 2200 RPM	22.30 (30.17) @ 2200 RPM	28 (37.96) @ 2800 RPM
COMPRESSION RATIO	6.8:1	6.6:1	7.3:1
DRY WEIGHT lbs.	71.0 (32.2)	129 (58.5)	129 (58.5)
OIL CAPACITY W/FILTER U.S. pints	2.50 (1.2)	4 (1.9)	4 (1.9)
OPTIONAL FUEL TANK U.S. quarts	5 (4.7)	5 (4.7)	5 (4.7)
LUBRICATION	Splash	Splash	Splash
*DIMENSIONS L x W x H	12.64" x 16.75" x 14.38"	13.45" x 20.92" x 18.66"	13.45" x 20.92" x 18.66"

\*Length/height includes recoil starter to PTO mounting face.

Horsepower ratings (shown as gross) are in accordance with Society of Automotive Engineers Small Engine Test Code J1995. Actual engine horsepower is lower and affected by, but not limited to, accessories (air cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed and ambient operating conditions (temperature, humidity and altitude). For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.